

British Manufacturing since 1957



The Professionals Choice

CTS10

SureFlow Counter-top, Automatic-Fill Water Boiler



FULL SPECIFICATION



SureFlow Automatic Fill Water Boiler

Туре	Countertop - Economy Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Capacity (Litres)	10
Unit dimensions (W x D x H) mm	243 x 510 x 610 (depth includes drip-tray)
Packed dimensions (W x D x H) mm	330 x 570 x 735
Tap clearance mm	190mm
Product weight - empty (kg)	12.1
Product weight – empty (kg) Product weight – full (kg)	24.9
Packed weight (kg)	16
CONSTRUCTION:	10
	204 grade Ctainless Ctael (Cuperbrush nalish)
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	2
Power rating (kW)	3
Voltage supply	220-230V (50-60Hz)
Electrical supply	Single-phase, N & E (13A)
Plug type	UK standard 3-pin
Fitted cable length (m)	1.7m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4" BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Front via drip-tray (or rear using kit not supplied)
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	32 mins (full tank capacity)
Output per hour (@ default temperature setting)	27 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	10 Litres
Recovery per minute	0.5 Litres
Stand-by power loss (idle mode)	0.1 kW/h
FILTRATION:	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	, , ,
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	
Early warning lime-scale diagnostics (via LED light)	Yes – Basic
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	, p
WRAS approved	Pending
EMC Tested and Certified (EN 55014 & EN 61000)	Yes
Electrical Safety Tested and Certified to BS standard	Yes
EN 60335-1 & 2	100
WARRANTY & AFTER-SALES:	
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
oparo parto, ilitero di accessorites	oamo day despaton (ii ordered betore spiri)

Instanta Limited T: 01704 501114 F: 01704 501115 E: sales@instanta.com



